

Pulley Blocks

0.5Ton-200Ton



with hook



with ring

Pulley is an important lifting tool which is convenient and simple in structure, with single wheel, double wheel, three wheel, four wheel and more wheels. Max capacity 200t. It can change direction of pulley, steel rope and high weight cargo, especially series of pulley combined with windlass, mast and other lifting machinery. It widely used in installation for construction. Its standard from 0.5-200T and wheels not exceed ten. Our lifting tools include hooks, chain rings, lifting ring, handing beam. You can choose it according to your need.

Specifications

Type	Capacity (t)	Test Load (kn)	Wire Rope Diameter (mm)		Sheave Diameter (mm)	Weight (kg)
			Apply	Max		
Single sheave pulley block	0.5	8	6.2	7.7	71	1.75
	1	16	7.7	11	85	3.25
	2	32	11	14	112	6
	3.2	51.2	12.5	15.5	132	10.5
	5	80	15.5	18.5	160	19
	8	128	20	23	210	35.2
	10	160	23	24.5	240	50.5
	16	224	28	31	315	113.5
2 sheaves pulley block	1	16	6.2	7.7	71	3.15
	2	32	7.7	11	85	6
	3.2	51.2	11	14	112	11
	5	80	12.5	15.5	132	20
	8	128	15.5	18.5	160	35
	10	160	17	20	180	47
	16	224	23	24.5	240	75.2
	20	280	26	28	280	138.9
3 sheaves pulley block	3.2	51.2	7.7	11	85	8.2
	5	80	11	14	112	16.83
	8	128	12.5	15.5	132	18
	10	160	15.5	18.5	160	47
	16	224	17	20	190	49.79
	20	280	20	23	210	69.59
	32	448	26	28	280	187.8

	50	700	31	35	355	360
4 sheaves pulley block	8	128	11	14	112	29.36
	10	160	12.5	15.5	132	41.46
	16	224	15.5	18.5	160	76.23
	20	280	17	20	180	84
	32	448	23	24.5	240	196.23
	50	700	28	31	315	347.9
5 sheaves pulley block	20	280	15.5	18.5	160	91.5
	32	448	20	23	280	303
	50	700	23	24.5	240	277.5
	80	1040	31	35	355	516.5
6 sheaves pulley block	32	448	17	20	180	122.73
	50	700	23	24.5	240	277.5
	80	1040	28	31	315	507.3
	100	1300	31	35	355	691.3
8 sheaves pulley block	80	1040	26	28	280	530
	100	1300	28	31	315	653.5
	160	2080	31	35	355	1137.4
	200	2500	34	38	400	1360
10 sheaves pulley block	200	2500	31	35	355	1552