

# 4WD Winches

## 5000LBS-20000LBS



### Specifications

Model	Capacity(lbs)	Motor(kw)	Voltage(V)	Gear reduction ratio	Gross weight(kgs)	Net weight(kgs)	Packing size(cm)	Package(pcs)	Mounting bolt pattern(mm)
4WDW5000	5000	1.2	12	218:1	26	24	49*19*34.5	1	166.4*114.3
4WDW6000	6000	1.3		218:1	27	25	49*19*34.5		166.4*114.3
4WDW6000	6000	4		218:1	28	26	49*19*34.5		166.4*114.3
4WDW8000	8000	4.13		218:1	35	33	57*19*34.5		254*114.3
4WDW8500	8500	4		195.8:1	37.5	35.5	57*19*34.5		254*114.3
4WDW9500	9500	4		195.4:1	38	36	57*19*34.5		254*114.3
4WDW10000	10000	4		148.2:1	39	37	57*19*34.5		254*114.3
4WDW12000	12000	4.8		187.2:1	39	37	57*19*34.5		254*114.3
4WDW13000	13000	4		218.4:1	39.5	37.5	57*19*34.5		254*114.3
4WDW13000	13000	4		24	218.4:1	40	38		57*19*34.5
4WDW15000	15000	4.2	312.4:1		55	53	60*23*38.5	254*114.3	
4WDW16800	16800	4.6	312.4:1		56	54	60*23*38.5	254*114.3	
4WDW20000	20000	5.5	375:1		78	54	/	254*194.3	

Drum size(m)	Gear train	Overall dimension(mm)	Cable	Battery leads	Finish
φ63.5*140	3 stage planetary	456*156*215	9/32" of 66ft diameter (Φ6.4mmx20m)	2 gauge, 72" (183mm)	black powder coated
φ63.5*140		456*156*215	9/32" of 66ft diameter (Φ7.2mmx20m)		
φ63.5*140		537*160*218	94ft of 5/16" diameter (28m of 8.1mm diameter)		
φ64*224		537*160*218	94ft of 5/16" diameter (28m of 8.1mm diameter)		
φ63.5**224		537*160*218	94ft of 5/16" diameter (28m of 8.1mm diameter)		
φ63.5**224		537*160*218	94ft of 5/16" diameter (28m of 8.3mm diameter)		
φ64*223.5		537*160*218	94ft of 5/16" diameter (28m of 8.3mm diameter)		
φ64*224		537*160*280	94ft of 3/8"diamdeter(28m of 9.4mm diameter)		
φ64*223		537*160*280	/		
φ64*223		540*160*218	Φ9.5mmX26m		
φ85*221.5		547*180*247	Φ11.0mmx28m(0.433"x91.86")		Dark gray powder coated
φ85*221.5		547*180*247	Φ11.5mm, 26m		
φ99*201.5		565*310*280	Φ13.5mmx30m		