

Wrap Machines
2Ton



Control Mode	PLC system
Voltage	AC220v/50Hz, 380V/50Hz
Wrapping Dimension	L500-1200mm*W500-1200mm
Max Wrapping Weight	2000kg
Turntable Power	0.40/0.75/1.5/2.2KW
Max Wrapping Height	1800/2100/2300/2500/2700mm
Lifter Motor Power	0.37KW
Rotation Speed	1~12rpm(adjustable)
Turntable Diameter	1500/1650/1800/2000mm
Lift Speed	3.2m/min(adjustable)
Turntable Start Mode	Slow start, Slow stop
Turntable Height	85mm
Release Film Mode	Blocking tensile Type
Spare Parts	Pre stretch film frame, coping, metal slope
Machine Weight	600~800kg
Machine Size	L255*W150*H237cm(standard type)
Packing Efficiency	20~40 loads/hour
Up-down Frame	Double chain, Up-down speed variable
Packing Material	LLDPE stretch film
Film Width	500mm
Film Thickness	17~35μm
Film Inside Diameter	76mm
Film Outer Diameter	≤280 mm
Film Tension	Variable
Percentage of Pre-stretch	0~25%
Carriage Speed	3m/min
Automatic Grade	Automatic
Auto Load Height Detection	Enabled by photoelectric sensor
Optional	Ramp
Noise	≤750dB
Condition	Moisture≤98%, Temperature0-40°C