Advantage :
1.Durable and rigid frame construction ensure the stackers to handle heavy loads.
2.Hourmeter and BDI(Battery Discharge Indicator)on time informs the operator of recharge requirements.
3.Sideway battery exchange to reduce intervals,ensure working efficiency and productivity.
4.Tilter head ergonomically designed for maximum opertor comfortable,and control buttons positioned to allow operation with either hand.
5.limit switch mounted on top of mast to precisely set the max.Lifting height,avoid any risk of lifting motor overload.
6.Robust and rigid mast configuration optimize stackers lifting stability and safety.

Model Number		TB215-45
Rated Capacity （Q）	kg	1500
Load Center (C)	mm	400
Max.Fork Height (H3)	m	4.5
Max.Machine Height (H4)	m	4.56
Handle Height (H2)	mm	1450~1460
Fork Size (1×n)	mm	1150×160
Fork Width (E)	mm	570(680)
Min.Turning Radius (Wa)	mm	1620
Wheel Base (Y)	mm	1340
Front-Wheel Distance (X)	mm	339
Max.Speed Without Load	km/h	4.5~6
Max.Speed With Load	km/h	4~5
Max.Climbing Capacity	%	8~10
Driving Motor	v/kw	24/1.2
Lifting Motor	v/kw	24/2~3
Overall Length	mm	2000
Overall Width	mm	860
Overall Height	m	2.58
Overall Net Weight	kg	740