

# Personal protective equipment against falls from a height — Retractable type fall arresters

The European Standard EN 360:2002 has the status of a  
British Standard

ICS 13.340.99

## National foreword

This British Standard is the official English language version of EN 360:2002. It supersedes BS EN 360:1993 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PH/5, Industrial safety belts and harnesses, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

### Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the *BSI Catalogue* under the section entitled "International Standards Correspondence Index", or by using the "Search" facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for their correct application.

**Compliance with a British Standard does not of itself confer immunity from legal obligations.**

This British Standard, having been prepared under the direction of the Health and Environment Sector Policy and Strategy Committee, was published under the authority of the Standards Policy and Strategy Committee on 4 July 2002

### Summary of pages

This document comprises a front cover, an inside front cover, the EN title page, pages 2 to 10, an inside back cover and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

### Amendments issued since publication

Amd. No.	Date	Comments

English version

## Personal protective equipment against falls from a height - Retractable type fall arresters

Équipement de protection individuelle contre les chutes de  
hauteur - Antichutes à rappel automatique

Persönliche Schutzausrüstung gegen Absturz -  
Höhensicherungsgeräte

This European Standard was approved by CEN on 15 March 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: rue de Stassart, 36 B-1050 Brussels**

## Contents

	page
Foreword.....	3
1 Scope .....	4
2 Normative references .....	4
3 Terms and definitions.....	4
4 Requirements .....	5
4.1 Design and ergonomics .....	5
4.2 Materials and construction .....	5
4.3 Locking .....	5
4.3.1 Locking after conditioning.....	5
4.3.2 Locking after optional conditioning.....	5
4.4 Static strength.....	5
4.5 Dynamic performance .....	6
4.6 Optional requirement concerning endurance.....	6
4.7 Corrosion resistance .....	6
4.8 Marking and information .....	6
5 Test methods.....	6
5.1 Locking test after conditioning .....	6
5.1.1 Apparatus .....	6
5.1.2 Method .....	6
5.2 Static strength test .....	7
5.2.1 Apparatus .....	7
5.2.2 Method .....	7
5.3 Dynamic performance test.....	7
5.3.1 Apparatus .....	7
5.3.2 Method .....	7
5.4 Endurance test .....	7
5.4.1 Apparatus .....	7
5.4.2 Method .....	7
5.5 Corrosion test.....	7
6 Marking .....	7
7 Information supplied by the manufacturer.....	8
8 Packaging .....	8
Annex ZA (informative) Clauses of this European Standard addressing essential requirements or other provisions of EU Directives .....	9
Bibliography .....	10

## Foreword

This document EN 360:2002 has been prepared by Technical Committee CEN/TC 160 "Protection against falls from a height including working belts", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by November 2002, and conflicting national standards shall be withdrawn at the latest by November 2002.

This document supersedes EN 360:1992. This new edition contains the old text of the standard and incorporates some urgent amendments that are intended to give additional information and clarify inconsistencies. A comprehensive revision of the standard will follow at a later stage.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For relationship with EU Directive(s), see informative annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

## 1 Scope

This European Standard specifies the requirements, test methods, marking, information supplied by the manufacturer and packaging for retractable type fall arresters. Retractable type fall arresters conforming to this European Standard are sub-systems constituting one of the fall arrest systems covered by EN 363, when combined with a full body harness specified in EN 361. Other types of fall arresters are specified in EN 353-1 and EN 353-2. Energy absorbers are specified in EN 355.

## 2 Normative references

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text, and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies (including amendments).

EN 354:2002, *Personal protective equipment against falls from a height – Lanyards.*

EN 355:2002, *Personal protective equipment against falls from a height – Energy absorbers.*

EN 362, *Personal protective equipment against falls from a height – Connectors.*

EN 363:2002, *Personal protective equipment against falls from a height – Fall arrest systems.*

EN 364:1992, *Personal protective equipment against falls from a height – Test methods.*

EN 365, *Personal protective equipment against falls from a height – General requirements for instructions for use and for marking.*

## 3 Terms and definitions

For the purposes of this European Standard, the following terms and definitions apply.

### 3.1

#### **retractable type fall arrester**

fall arrester with a self-locking function and an automatic tensioning and return facility for the lanyard, i.e. the retractable lanyard. An energy dissipating function may be incorporated in the device itself or an energy absorber may be incorporated in the retractable lanyard [EN 363]

### 3.2

#### **retractable lanyard**

connecting element of a retractable type fall arrester. A retractable lanyard may be of wire rope, webbing or synthetic fibre rope and may be longer than 2 m [EN 363]

### 3.3

#### **energy absorber**

element or a component of a fall arresting system, which is designed to dissipate the kinetic energy developed during a fall from a height [EN 363]

### 3.4

#### **braking force**

maximum force  $F_{\max}$  in kilonewtons measured at the anchor point or the anchor line during the braking period of the dynamic performance test [EN 363]

### 3.5

#### **arrest distance**

vertical distance  $H$  in metres measured at the mobile load bearing point of the connecting sub-system from the initial position (onset of the free fall) to the final position (equilibrium after the arrest), excluding the displacements of the full body harness and its attachment element [EN 363]

## 4 Requirements

### 4.1 Design and ergonomics

The general requirements for the design and ergonomics are specified in 4.1 of EN 363:2002.

A retractable type fall arrester may comprise a drum around which the retractable lanyard reels or unreels, or a return pulley with counterweights.

### 4.2 Materials and construction

The retractable lanyard shall be a wire rope, a webbing or a synthetic fibre rope. The material of a retractable lanyard shall conform to 4.2.2 and 4.2.3 of EN 354:2002.

It shall be confirmed by the static strength test specified in 5.2 that the internal end of the retractable lanyard is suitably secured to the device.

The external end of the retractable lanyard shall be suitably terminated.

Energy absorbers not integrated in the retractable lanyard shall conform to EN 355. Energy absorbers integrated in the retractable lanyard shall conform to EN 355, but need not be tested in accordance with 5.2 of EN 355:2002.

Connectors for retractable type fall arresters shall conform to EN 362 and shall incorporate a swivel function.

### 4.3 Locking

#### 4.3.1 Locking after conditioning

When conditioned as described in 5.1.2.1 and tested as described in 5.1.2.3 with a minimum test mass of 5 kg, the retractable type fall arrester shall in each case lock and remain locked until released.

#### 4.3.2 Locking after optional conditioning

If the marking on the retractable type fall arrester and the information supplied by the manufacturer (see clauses 6 and 7) claims a feature concerning the use under specific conditions (see 5.1.2.2), the locking function of the retractable type fall arrester shall be tested accordingly.

When conditioned as described in 5.1.2.2 and tested as described in 5.1.2.3 with a minimum test mass of 5 kg, the retractable type fall arrester shall in each case lock and remain locked until released.

### 4.4 Static strength

Retractable type fall arresters with a retractable lanyard made from synthetic fibre rope or webbing shall sustain a force of at least 15 kN when tested as described in 5.2.

Retractable type fall arresters with a retractable lanyard made from wire rope shall sustain a force of at least 12 kN when tested as described in 5.2.

#### 4.5 Dynamic performance

When tested as described in 5.3.2 with a rigid steel mass of 100 kg, the braking force  $F_{\max}$  shall not exceed 6 kN and the arrest distance  $H$  shall not exceed 2 m.

#### 4.6 Optional requirement concerning endurance

If the marking on the retractable type fall and the information supplied by the manufacturer (see clauses 6 and 7) claims the feature concerning endurance, the retractable type fall arrester shall be tested as described in 5.4 with a total of 1 000 relative movements.

#### 4.7 Corrosion resistance

After tested as described in 5.5 the elements of the retractable type fall arrester shall be examined. Where necessary to gain visual access to the internal elements, the device shall be dismantled. The test is classed as a failure if any corrosion is evident that could affect the function of the device. (White scaling or tarnishing is acceptable.)

#### 4.8 Marking and information

Marking of the retractable type fall arrester shall be in accordance with clause 6.

Information shall be supplied with the retractable type fall arrester in accordance with clause 7.

### 5 Test methods

#### 5.1 Locking test after conditioning

##### 5.1.1 Apparatus

##### 5.1.1.1 Apparatus for conditioning

The conditioning apparatus shall conform to 4.8 of EN 364:1992.

##### 5.1.1.2 Apparatus for the locking test

The locking test apparatus shall consist of an anchor point and a minimum test mass of 5 kg according to 5.11.6.2 of EN 364:1992.

##### 5.1.2 Method

##### 5.1.2.1 Conditioning

The conditioning to heat, to cold and to wet is described in 5.11 of EN 364:1992.

##### 5.1.2.2 Optional conditioning

The conditioning to dust and to oil is optional and described in 5.11 of EN 364:1992.

##### 5.1.2.3 Locking test

The locking test shall be conducted as described in 5.11.6.2 of EN 364:1992.



## 5.2 Static strength test

### 5.2.1 Apparatus

The static strength apparatus shall conform to 4.1 of EN 364:1992.

### 5.2.2 Method

The static strength test shall be conducted as described in 5.7.4 of EN 364:1992.

## 5.3 Dynamic performance test

### 5.3.1 Apparatus

The dynamic performance test apparatus shall conform to 4.4, 4.5 and 4.6 of EN 364:1992.

### 5.3.2 Method

The dynamic performance test shall be conducted as described in 5.7.2 of EN 364:1992.

## 5.4 Endurance test

### 5.4.1 Apparatus

The endurance test apparatus shall conform to 4.9 of EN 364:1992.

### 5.4.2 Method

The endurance test shall be conducted as described in 5.12.2 of EN 364:1992.

## 5.5 Corrosion test

The corrosion test shall be conducted as described in 5.13 of EN 364:1992 for a minimum period of 24 h.

## 6 Marking

Marking on the retractable type fall arrester shall conform to 2.2 of EN 365:1992 and any text shall be in the languages of the country of destination. In addition to conforming to 2.2 of EN 365:1992 the marking shall include the following:

- a) on the retractable type fall arrester, a pictogram to indicate that users shall read the information supplied by the manufacturer (see figure);



- b) the specific conditions under which a retractable type fall arrester may be used, e.g. vertical, horizontal or inclined;
- c) the model/type identification mark of the retractable type fall arrester;

## EN 360:2002 (E)

- d) the number of this European Standard, i.e. EN 360.

### 7 Information supplied by the manufacturer

The information supplied by the manufacturer shall be provided in the languages of the country of destination. It shall conform to 2.1 of EN 365:1992 and in addition shall include at least advice or information as follows:

- a) the specific conditions under which the retractable type fall arrester may be used, e. g. vertical, horizontal or inclined;
- b) the characteristics required for a reliable anchor point;
- c) the correct way of connecting to a reliable anchor point, to a full body harness and to other components of a fall arrest system;
- d) on how to ensure the compatibility of any components to be used in conjunction with the retractable type fall arrester, e.g. by reference to other European Standards;
- e) if a complete system is supplied, that components of any complete system shall not be substituted;
- f) the correct way of operating the retractable type fall arrester;
- g) the necessary minimum clearance below the feet of the user, in order to avoid collision with the structure or ground in a fall from a height. With a mass of 100 kg the clearance is the arrest distance  $H$  (see 3.5) plus an extra distance of 1 m;
- h) the materials from which the retractable lanyard is made;
- i) on limitations of the materials in the product or hazards which may affect its performance, e.g. temperature, the effect of sharp edges, chemical reagents, electrical conductivity, cutting, abrasion, UV degradation, other climatic conditions;
- j) that before and during use, consideration should be given as to how any rescue could be safely and efficiently carried out;
- k) that the product should only be used by a trained and/or otherwise competent person or the user should be under the direct supervision of such a person;
- l) on how to clean the product, including disinfection, without adverse effect;
- m) if information exists, the expected lifespan of the product (obsolescence) or how this may be determined;
- n) on how to protect the product during transportation;
- o) the model/type identification mark of the retractable type fall arrester;
- p) on the meaning of any markings on the product;
- q) the number of this European Standard, i.e. EN 360.

### 8 Packaging

Retractable type fall arresters shall be supplied wrapped, but not necessarily sealed, in a material that provides some resistance against the penetration of moisture.

## Annex ZA (informative)

### Clauses of this European Standard addressing essential requirements or other provisions of EU Directives

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association and supports essential requirements of EU Directive 89/686/EEC.

**WARNING** : Other requirements and other EU Directives may be applicable to the product(s) falling within the scope of this European Standard.

The following clauses of this European Standard are likely to support requirements of Directive 89/686/EEC, Annex II :

EU-Directive 89/686/EEC, Annex II	clauses of this standard
1.1 Design principles	4.1 and 4.2
1.2 Innocuousness of PPE	4.2
1.3.2 Lightness and design strength	4.4, 4.5 and 4.6
1.4 Information supplied by the manufacturer	4.8 and 7
2.1 PPE incorporating adjustment systems	7
2.12 PPE bearing one or more identification or recognition marks directly or indirectly relating to health and safety	6
3.1.2.2 Prevention of falls from height	4.3, 4.5 and 7

Compliance with the clauses of this European Standard provides one means of conforming to the specific essential requirements of the Directive concerned and associated EFTA regulations.

## Bibliography

EN 353-1, *Personal protective equipment against falls from a height – Part 1: Guided type fall arresters including a rigid anchor line.*

EN 353-2, *Personal protective equipment against falls from a height – Part 2: Guided type fall arresters including a flexible anchor line.*

EN 361, *Personal protective equipment against falls from a height – Full body harnesses.*



---

---

## BSI — British Standards Institution

BSI is the independent national body responsible for preparing British Standards. It presents the UK view on standards in Europe and at the international level. It is incorporated by Royal Charter.

### Revisions

British Standards are updated by amendment or revision. Users of British Standards should make sure that they possess the latest amendments or editions.

It is the constant aim of BSI to improve the quality of our products and services. We would be grateful if anyone finding an inaccuracy or ambiguity while using this British Standard would inform the Secretary of the technical committee responsible, the identity of which can be found on the inside front cover. Tel: +44 (0)20 8996 9000. Fax: +44 (0)20 8996 7400.

BSI offers members an individual updating service called PLUS which ensures that subscribers automatically receive the latest editions of standards.

### Buying standards

Orders for all BSI, international and foreign standards publications should be addressed to Customer Services. Tel: +44 (0)20 8996 9001. Fax: +44 (0)20 8996 7001. Email: [orders@bsi-global.com](mailto:orders@bsi-global.com). Standards are also available from the BSI website at <http://www.bsi-global.com>.

In response to orders for international standards, it is BSI policy to supply the BSI implementation of those that have been published as British Standards, unless otherwise requested.

### Information on standards

BSI provides a wide range of information on national, European and international standards through its Library and its Technical Help to Exporters Service. Various BSI electronic information services are also available which give details on all its products and services. Contact the Information Centre. Tel: +44 (0)20 8996 7111. Fax: +44 (0)20 8996 7048. Email: [info@bsi-global.com](mailto:info@bsi-global.com).

Subscribing members of BSI are kept up to date with standards developments and receive substantial discounts on the purchase price of standards. For details of these and other benefits contact Membership Administration. Tel: +44 (0)20 8996 7002. Fax: +44 (0)20 8996 7001. Email: [membership@bsi-global.com](mailto:membership@bsi-global.com).

Information regarding online access to British Standards via British Standards Online can be found at <http://www.bsi-global.com/bsonline>.

Further information about BSI is available on the BSI website at <http://www.bsi-global.com>.

### Copyright

Copyright subsists in all BSI publications. BSI also holds the copyright, in the UK, of the publications of the international standardization bodies. Except as permitted under the Copyright, Designs and Patents Act 1988 no extract may be reproduced, stored in a retrieval system or transmitted in any form or by any means – electronic, photocopying, recording or otherwise – without prior written permission from BSI.

This does not preclude the free use, in the course of implementing the standard, of necessary details such as symbols, and size, type or grade designations. If these details are to be used for any other purpose than implementation then the prior written permission of BSI must be obtained.

Details and advice can be obtained from the Copyright & Licensing Manager. Tel: +44 (0)20 8996 7070. Fax: +44 (0)20 8996 7553. Email: [copyright@bsi-global.com](mailto:copyright@bsi-global.com).